



# Rustic Finish

FIN.RUST

FIN.RUST.PLUS

Natural Calk rustic finish has the aesthetic effect of a trowelled or spot-coated civil plaster, consisting of cured lime putty according to UNI EN 459-1 and selected aggregates and mineral dyes, without cements and chemical additives.



LAB N° 1035L



## Product Description

The Natural Calk rustic finish is ideal for giving facades a rustic effect, and is perfectly suited for even modern works. To ensure bonding to the substrate, a pre-consolidation with Natural Calk Fixative F.S.P.1 substance is recommended; the Natural Calk smoothing mortar can be applied on:

Raw walls completely finished; civil plaster;

To regularize old walls;

Filling and grouting, finishes on ancient exposed brick walls;

It is applied to cork, calcium silicate, cellular concrete, wood cement, aspen-aerogel, plasterboard and magnesium calcium. TYPE F: fine aggregates. TYPE G: large aggregates.

## Rules of use and recommendations

The Natural Calk rustic finish is applied with a steel trowel; when it starts to adhere, it must be finished with a sponge trowel;

For other applications, just finish with a steel trowel; Protect the application from rain for about 48 hours;

The company takes on solely responsibility for the product up to the departure of the material from our deposit, while the application, use and processing are the exclusive responsibility of the customer or the applicator.

The company reserves to modify the composition keeping the characteristics naturally unchanged We decline all responsibility for the incorrect use and application of materials other than those recommended from the Natural Calk Line



# Rustic Finish

FIN.RUST

FIN.RUST.PLUS

Natural Calk rustic finish has the aesthetic effect of a trowelled or spot-coated civil plaster, consisting of cured lime putty according to UNI EN 459-1 and selected aggregates and mineral dyes, without cements and chemical additives.



LAB N° 1035L



Do not apply at air temperatures below 5°C or above 25°C and on masonry overheated by the sun; in hot and windy periods, it is necessary to moisten the walls;

Before use, shake mechanically until the mixture is homogeneous.

**RUSTIC FINISH PLUS (FIN.RUST.PLUS)** is applied for non-absorbent, smooth, ferrous and painted surfaces, polystyrene, plastic, and plasterboard.

## Yield

The yield of the Natural Calk rustic finish is on average 2 kg/sqm one coat, on civil plaster. The average coatings per coat consumption is 1.2 kg/sqm by coat.

In the walls for historical recovery, it varies according to the type of wall. Supplied in 25 kg drums.

## Features

The Natural Calk rustic finish differs because

- It is ready to use;
- It adheres perfectly; It resists alkaline aggression;
- It resists bacterial aggression from moulds and mosses; It offers effective abrasion resistance;
- It is not flammable;
- Wet specific weight 1.6 kg/l; Vapour permeability  $\mu 6$ ;
- Transmissivity W 1.8 - PH 12.

The company takes on solely responsibility for the product up to the departure of the material from our deposit, while the application, use and processing are the exclusive responsibility of the customer or the applicator.

The company reserves to modify the composition keeping the characteristics naturally unchanged We decline all responsibility for the incorrect use and application of materials other than those recommended from the Natural Calk Line

SMOOTHING SUBSTANCE



# Rustic Finish

FIN.RUST

FIN.RUST.PLUS

Natural Calk rustic finish has the aesthetic effect of a trowelled or spot-coated civil plaster, consisting of cured lime putty according to UNI EN 459-1 and selected aggregates and mineral dyes, without cements and chemical additives.



LAB N° 1035L



## Specification item

Natural Calk rustic finish for stone facades and exposed brick and plasters, composed of naturally seasoned lime putty obtained by firing limestone with soft flame (wood), selected aggregates and mineral pigments, guaranteed free from cement and chemical additives.

VOC free

Water vapour permeability: V1 Liquid water permeability: W1

Price per sqm/€ \_\_\_\_ excluding scaffolding

The company takes on solely responsibility for the product up to the departure of the material from our deposit, while the application, use and processing are the exclusive responsibility of the customer or the applicator.

The company reserves to modify the composition keeping the characteristics naturally unchanged We decline all responsibility for the incorrect use and application of materials other than those recommended from the Natural Calk Line

**Arte e Mestieri**

Via Missionari Casarsesi, 15 33072 Casarsa della Delizia (PN)  
info@naturalcalk.com

 **Naturalcalk**